



APLIKLED

8 W Up/Down LED Wall Mount Sconce

Order Code : 3057140
Product Code : APL 008U 57CM00 31 CIFT



Product Data


Standard Features

Housing	: RAL 9005 Powder finished aluminium housing
Diffuser	: Transparent glass with tempered
Optic	: 31° lens
IP Grade	: IP66
Installation	: Surface mounted
Light Source	: Power LED

Optical & Electrical Features

Power Consumption	: 8 W
Final Luminous Flux	: 639.5 lm
Efficacy	: 79.4 lm/W
Input Voltage	: 220-240V AC
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Drive Current	: 350 mA
Correlated Color Temperature	: 5700K
Color Rendering Index	: >70

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -20 °C/+30 °C
Impact Resistance	: IK02
Led Life Time - L70	: > 60.500 hours @Ta= 30 °C


Optional Features

Correlated Color Temperatures	: 3000K, 4000K
Color Option	: RAL 9006, RAL 9007

APLIKLED

8 W Up/Down LED Wall Mount Sconce

3057140 APL 008U 57CM00 31 CIFT



Dimensions (mm)


	Ø	b	h
Standard	80	115	225

Weight (kg)


Standard	1,3
----------	-----




11 Degrees Photometric Curve



18 Degrees Photometric Curve



44 Degrees Photometric Curve



- EAE Aydınlatma reserves the right to make any change without prior notice.



Revision date: 02.06.2018