



ORI SMALL

Recessed Mounted 12 W Spot LED Luminaire

Order Code : 3239109
Product Code : ORI 012A 40SD00 24 LLL 20 SML YV FLP



Product Data

Standard Features


Housing	: Aluminium housing
Diffuser	: Transparent diffuser
Ceiling Type	: Plasterboard
IP Grade	: IP20
Installation	: Recessed mounted
Light Source	: COB LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 12 W
Final Luminous Flux	: 1118,56 lm
Efficacy	: 90,56 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is $\pm 10\%$ Tolerance in Technical Values.

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Impact Resistance	: IK02
Led Life Time - L70	: > 72.000 saat @Ta= 35 °C


Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: No
DALI Option	: No
Degree Option	: 36°

ORI SMALL


Recessed Mounted 12 W Spot LED Luminaire

3239109 ORI 012A 40SD00 24 LLL 20 SML YV FLP



Dimensions (mm)

	a	b	h
Standart	58	100	52



- EAE, reserves the right to make changes without prior notice.



Revision date: 27.07.2022