



ORI

Recessed Mounted 20 W Spot LED Luminaire

Order Code : 3200752
Product Code : ORI 020A 40SD00 24 2K3 20 YV FLP



Product Data

Standard Features


| | |
|--------------------|---------------------|
| Housing | : Aluminium housing |
| Diffuser | : 24° Reflector |
| Ceiling Type | : Plasterboard |
| IP Grade | : IP20 |
| Installation | : Recessed mounted |
| Light Source | : COB LED |
| Electronic Control | : On/Off |

Optical & Electrical Features

| | |
|------------------------------|----------------|
| Power Consumption | : 20 W |
| Final Luminous Flux | : 2320 lm/W |
| Efficacy | : 116 lm/W |
| Input Voltage | : 220-240 V AC |
| Frequency | : 50-60 Hz |
| Power Factor | : Cos Ø > 0,9 |
| Correlated Color Temperature | : 4000K |
| Color Rendering Index | : >80 |

* There is ± 10% Tolerance in Technical Values.

Photometric Curve



Other Features & Conditions

| | |
|-----------------------------|-----------------------------|
| Operating Temperature Range | : -5 °C / +35 °C |
| Impact Resistance | : IK02 |
| LED Life Time - L70 | : > 60.000 hours @Ta= 35 °C |

Optional Features

| | |
|-------------------------------|-----------------|
| Correlated Color Temperatures | : 3000K / 6500K |
| Emergency Kit Options | : 1 / 3 hours |
| DALI Option | : Yes |
| Degree Option | : 40° / 60° |




ORI

Recessed Mounted 20 W Spot LED Luminaire

3200752 ORI 020A 40SD00 24 2K3 20 YV FLP

Dimensions (mm)

| | \varnothing | h | $\varnothing D$ |
|----------|---------------|-----|-----------------|
| Standard | 119 | 135 | 108 |



- EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY
Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90
www.eaeaydinlatma.com.tr

Revision date: 07.12.2020