



TORNADO

Surface Mounted 34 W Etanj LED Luminaire

Order Code : 3287075
Product Code : TRD 034U 400D00 4K88 120 66 ELP



Product Data

Standard Features


Housing	: Grey PC (high mechanical resistance, UV stability)
Diffuser	: Translucent PC with nanooptics (high mechanical resistance, UV stability)
IP Grade	: IP66
Installation	: Surface mounted
Light Source	: Mid Power LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 33,8 W
Final Luminous Flux	: 4887,6 lm
Efficacy	: 144,2 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is $\pm 10\%$ tolerance in Technical Values

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -25 °C/+35 °C
Impact Resistance	: IK08
Led Life Time - L90B10	: > 102.000 hours @Ta=35°C

Optional Features

Correlated Color Temperatures	: 3000K, 5000K , 6500K
Emergency Kit Options	: 1, 3 hours



TORNADO

Surface Mounted 34 W Etanj LED Luminaire



3287075 TRD 034U 400D00 4K88 120 66 ELP

Dimension (mm)

	a	b	h	d
Standard	1175	98	84	700-960



1064641: TRD ASKI TAKIM KANCASI



- EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.

İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90
www.eaeaydinlatma.com.tr