



Surface Mounted 20W Spot LED Luminaire



Housing	: Aluminium Housing
Optic	: 80° Lens + Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP65
Installation	: Surface Mounted
Light Source	: SMD LED
Electronic Control	: On/Off

Power Consumption	: 20W
Final Luminous Flux	: 2079lm
Efficacy	: 103,9 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

Photometric Curve




Emergency Kit Options	: No
DALI Option	: Yes
Degree Option	: 50°

Operating Temperature Range	: -5 °C / +35 °C
Impact Resistance	: IK03
Led Life Time - L70	: > 72.000 hours @Ta= 35 °C

GIZA V.2 IP65

Surface Mounted 20W LED Luminaire

3293040 GZA 020U 40LN00 80 2K1 65 FLP



Dimensions (mm)

	a X b	a1 X b1	h	h1
Standard	105 x 105	70 X 70	100	20

Weight (kg)

Standard	1.450
----------	-------



- EAE, reserves the right to make changes without prior notice.



Revision date: 16.02.2023