



BELLA 2X

Surface Mounted 20 W Spot LED Luminaire

Order Code : 3249447
Product Code : BLL 020U 40SD00 36 2K1 20 2X FLP



Product Data

Standard Features


Housing	: Aluminium housing
Optic	: 36° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP20
Installation	: Surface Mounted
Light Source	: COB LED
Electronic Control	: On-Off

Optical & Electrical Features

Power Consumption	: 20 W
Final Luminous Flux	: 2120 lm
Efficacy	: 106 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

*There is ±%10 tolerance in the technical values.

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Impact Resistance	: IK03
Led Life Time - L70	: 72.000 saat @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: None
DALI Option	: Yes
Degree Option	: 24° / 60°

BELLA 2X

Surface Mounted 20 W Spot LED Luminaire


3249447 BLL 020U 40SD00 36 2K1 20 2X FLP

Dimensions (mm)

	a	b	h
Standart	100	200	130

Weight (kg)

Standard	1.950
----------	-------



- EAE, reserves the right to make changes without prior notice.



EAE Aydınlatma A.Ş.

İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY

Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90

www.eaeaydinlatma.com.tr

Revision date: 05.12.2022