



## KRIZA V.2

Recessed Mounted 36 W Spot LED Luminaire

Order Code : 3236291  
Product Code : KRZ 036A 40SD00 60 4K2 1X V.2 FLP



### Product Data

#### Standard Features


Housing	: Aluminium injection housing
Diffuser	: 60° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP20
Installation	: Recessed mounted
Light Source	: COB LED
Electronic Control	: On/Off

#### Optical & Electrical Features

Power Consumption	: 36 W
Final Luminous Flux	: 4176lm
Efficacy	: 116 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos $\phi$ > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

\* There is  $\pm$  10% Tolerance in Technical Values.

### Photometric Curve



#### Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Operating Temperature Range With	: +10 °C / +35 °C
Emergency Kit	
Impact Resistance	: IK03
Led Life Time - L70	: 72.000 hours @Ta= 35 °C

#### Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: 1 / 3 hours
DALI Option	: Yes
Degree Option	: 24° / 40°



## KRIZA V.2

Recessed Mounted 36 W Spot LED Luminaire

3236291 KRZ 036A 40SD00 60 4K2 1X V.2 FLP


### Dimensions (mm)

	a	b	h	d1xd2
Standard	155	155	120	140x140



### Weight (kg)

Standart	1.400
----------	-------



- EAE, reserves the right to make changes without prior notice.

**engineering the light**

EAE Aydınlatma A.Ş.

İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY

Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90

www.eaeaydinlatma.com.tr

Revision date: 05.12.2022