



LORY IP65

Recessed Mounted 20 W Spot LED Luminaire

Order Code : 3266869
Product Code : LRY 020A 40CM00 36 1K8 65 YV FLP



Product Data

Standard Features

Housing	: Aluminium Housing
Optic	: 36° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP65
Installation	: Recessed Mounted
Light Source	: COB LED
Electronic Control	: On-Off

Optical & Electrical Features


Power Consumption	: 20 W
Final Luminous Flux	: 1820 lm
Efficacy	: 91 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos ϕ > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

*There is \pm 10 tolerance in the technical values.

Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Operating Temperature Range With Emergency Kit	: +5 °C / +35 °C
Impact Resistance	: IK03
Led Life Time - L70	: 72.000 saat @Ta= 35 °C

Photometric Curve



Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: 1 / 3 Hours
DALI Option	: Yes
Degree Option	: 24° / 60°



LORY IP65

Recessed Mounted 20 W Spot LED Luminaire


3266869 LRY 020A 40CM00 36 1K8 65 YV FLP

Dimensions (mm)


	Ø	h	ØD
Standard	96	110	86



On-Off / DALI Driver IP65 Box



On-Off / DALI Driver +
Emergency Kit IP65 Box



- EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY
Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90
www.eaeaydinlatma.com.tr

Revision date: 19.02.2024