



Recessed Mounted 6 W Spot LED Luminaire



Photometric Curve

Power Consumption	: 6 W
Final Luminous Flux	: 678 lm
Efficacy	: 113 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Operating Temperature Range With Emergency Kit	: +5 °C / +35 °C
Impact Resistance	: IK03
Led Life Time - L70	: 72.000 saat @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 2700 / 3000K / 6500K
Emergency Kit Options	: 1 / 3 hours
DALI Option	: Yes
Degree Option	: 24°



ORI-Y MINI

Recessed Mounted 6 W Spot LED Luminaire

3238481 ORI 006A 40SD00 36 0K7 20 MN YV FLP

Dimensions (mm)

	Ø	h	ØD
Standard	85	115	76



Weight (kg)

Standard	0.290
----------	-------

- EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY
Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90
www.eaeaydinlatma.com.tr

Revision date: 04.07.2023