



Recessed Mounted 8 W Spot LED Luminaire



Housing	: Aluminium Housing
Optic	: 36° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP20
Installation	: Recessed Mounted
Light Source	: COB LED
Electronic Control	: On/Off

Power Consumption	: 8 W
Final Luminous Flux	: 853 lm
Efficacy	: 106.6 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

Photometric Curve



Correlated Color Temperatures	: 2700 / 3000K / 6500K
Emergency Kit Options	: 1 / 3 hours
DALI Option	: Yes
Degree Option	: 24°



ORI-Y MINI

Recessed Mounted 8 W Spot LED Luminaire

3238545 ORI 008A 40SD00 36 0K9 20 MN YV FLP

Dimensions (mm)

	Ø	h	ØD
Standard	85	115	76



Weight (kg)

Standard	0.290
----------	-------

- EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.

İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL -TURKEY

Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90

www.eaeaydinlatma.com.tr

Revision date: 04.07.2023