



ORI MESH SMALL

Open Cell 10 W Spot LED Luminaire

Order Code : 3325584
Product Code : ORI 010H 40SD00 36 1K0 20 SML FLP



Product Data

Standard Features


Housing	: Aluminium Housing
Optic	: 36° Reflector
Ceiling Type	: Open Cell
IP Grade	: IP20
Installation	: Open Cell
Light Source	: COB LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 10 W
Final Lumens Flux	: 954 lm
Efficacy	: 95.4 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is $\pm 10\%$ Tolerance in Technical Values.

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Impact Resistance	: IK03
Led Life Time - L70	: > 72.000 saat @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: Yes
DALI Option	: Yes
Degree Option	: 24°



ORI MESH SMALL

Open Cell 10 W Spot LED Luminaire

3325584 ORI 010H 40SD00 36 1K0 20 SML FLP

Dimensions (mm)


	a	b	h	h1
Standart	57	57	100	15



Weight (kg)

Standard	0.220
----------	-------

Mesh Tavan



- EAE, reserves the right to make changes without prior Yestice.

engineering the light

EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY
Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90
www.eaeaydinlatma.com.tr

Revision date: 10.05.2024