



SATURN MINI

Surface Mounted 12 W LED Lighting Luminaire

Order Code : 3178316
Product Code : STR 012U 400D00 1K2 20 V.MN



Product Data

Standard Features

Housing	: Plastic housing
Diffuser	: Opal diffuser
IP Grade	: IP20
Installation	: Surface mounted
Light Source	: Mid Power LED


Optical & Electrical Features

Power Consumption	: 12.2 W
Final Luminous Flux	: 1294.7 lm
Efficacy	: 106 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Surge Transient Protection	: 1 kV
Drive Current	: 350 mA
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

Other Features & Conditions

Operating Temperature Range	: -20 °C/+30 °C
Impact Resistance	: IK10
Led Life Time - L70	: > 72.000 hours @ Ta=30 °C

Photometric Curve




Optional Features

Correlated Color Temperatures	: 3000K, 5700K
Sensor	: Yes (Detection Area 4x4m)

SATURN MINI

Surface Mounted 12 W LED Lighting Luminaire

3178316 STR 012U 40OD00 1K2 20 V.MN



Dimensions (mm)

	\varnothing	h
Standard	262	70



Weight (kg)

Standard	635 g
Sensor	635 g

- EAE Aydınlatma reserves the right to make any change without prior notice.



Revizyon tarihi: 27.06.2019